


Caja Empalme Ideal Cat-6(250Mhz)



General data

Cat.6 connection module up to 250 MHz with IDC-terminals. The connecting module can be used to extend installation cables or reconnect damaged cables without having to install a complete cable segment.

With adhesive tapes for fixing

Screw-type strain relief

Cable entry up to 7.5 mm

Accessory

Screw-type strain relief (M3x12)

Cable inlet (4 x)

With adhesive tapes for fixing

Allgemeine Daten

Suitable for litz wire conductor	False
AWG-range	26 - 22
Max. cable diameter	10.0 mm
Current Rating	1,5 A
Suitable for degree of protection (IP)	IP20
Suitable for solid core	True
Connection type	LSA
Suitable for flat cable	False
Special tool necessary	False
Suitable for round cable	True
Category	6
Complaint to UL94	V-0

Caja Empalme Ideal Cat-6(250Mhz)

Mechanische Eigenschaften

Housing material	Plastic
Dust cover	false
Type of locking	Rastverriegelung
360° shield contact	True
Shield contact and strain relief separate	False

Elektrische Eigenschaften

Contact Resistance	20 mΩ
Dielectric Withstanding Voltage	1000 V AC 60Hz
Insulation Resistance	500 MΩ
screened	True

