

# CABLE DE RED C14/C15 3X0.75MM.



## Description

Plug IEC60320/C14 to jack IEC60320/C15  
10 A / 250 V VDE tested  
Colour black  
International standardised connectors

## General data

Connection 1	Cold device plug (IEC 320)
Connection 2	Hot device plug, female
Number of cores	3
Spiralized cable	False
Protective conductor	True
With cord switch	False
Colour outer sheath	Black

## Cable sheath

Material outer sheath	PVC
Temperature resistance	70 - 120 °C

## Electrical characteristics

Nominal voltage	250 V
-----------------	-------

## Standards, approvals, certifications

Oil resistant (acc. EN 60811-2-1)	False
Ölbeständig nach EN 60811-404	False

## Available variants

Article no.	Title	Nominal cross section conductor	Outer diameter approx.	Length
CAB585.1	Extension Cable C14 180° - C15 180°, black, 1.0 m, 3 x 0.75 mm <sup>2</sup>	0.75 mm <sup>2</sup>	6.8 mm	1.0 m
CAB585.2	Extension Cable C14 180° - C15 180°, black, 2.0 m, 3 x 0.75 mm <sup>2</sup>	0.75 mm <sup>2</sup>	6.8 mm	2.0 m
CAB585.3	Extension Cable C14 180° - C15 180°, black, 3.0 m, 3 x 0.75 mm <sup>2</sup>	0.75 mm <sup>2</sup>	6.8 mm	3.0 m

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.