

Fuente de luz de fibra óptica (SM) 1310/1550nm



General data

Fiber Optical Light Source 1310nm and 1550nm to use with item HS15-MESS. In combined use this units are for measuring IL attenuation of Singlemode fiber transmission link.

Specifications:

Wavelength: 1310nm/ 1550nm +/-10nm
Power Stability: +/-0,05db for 1 hour, +/- 0,1dB for 8 hours
Output Power: > -5dBm
Optic Connector: SC/PC
Signal Modulation: 270Hz, 1kHz, 2kHz
Low Battery warning
Storage Temperature: -20°C ~ +70°C
Storage Humidity: < 90%RH
Operating Temperature: -10°C ~ +60°C
Operating Humidity: < 90%RH
Power Source: 2x 1,5V AA batteries (not included)
Dimension: 165x80x35mm
Weight: 280g

Allgemeine Daten

Type of indication	LCD/monitor
--------------------	-------------

Fuente de luz de fibra óptica (SM) 1310/1550nm

Power	2 x AA
Available Connector	LC
Measured value memory	False
Suitable for network protocol measurement	False
With PC/printer interface	False

Abmessungen

Net weight	280 g
Dimension	165 x 80 x 35 mm

Umgebungsbedingungen

Storage Temperature	-20 - 70 °C
Operating Temperature	-10 - 60 °C

Übertragungstechnische Eigenschaften

Wavelength	1310 - 1550 nm
------------	----------------