

Fuente de luz de fibra óptica (MM) 850/1300nm



General data

Fiber Optical Light Source 850nm and 1300nm to use with item HS15-MESS. In combined use this units are for measuring IL attenuation of Multimode fiber transmission link.

Specifications:

Wavelength: 850nm/ 1300nm +/-10nm
Power Stability: +/-0,05db for 1 hour, +/- 0,1dB for 8 hours
Output Power: >-10dBm
Optic Connector: SC/PC
Signal Modulation: 270Hz, 1kHz, 2kHz
Low Battery warning
Storage Temperature: -20°C ~ +70°C
Storage Humidity: < 90%RH
Operating Temperature: -10°C ~ +60°C
Operating Humidity: < 90%RH
Power Source: 2x 1,5V AA batteries (not included)
Dimension: 165x80x35mm
Weight: 280g

Allgemeine Daten

| | |
|--------------------|-------------|
| Type of indication | LCD/monitor |
|--------------------|-------------|

Fuente de luz de fibra óptica (MM) 850/1300nm

| | |
|---|--------|
| Power | 2 x AA |
| Available Connector | LC |
| Measured value memory | False |
| Suitable for network protocol measurement | False |
| With PC/printer interface | False |

Abmessungen

| | |
|------------|------------------|
| Net weight | 280 g |
| Dimension | 165 x 80 x 35 mm |

Umgebungsbedingungen

| | |
|-----------------------|-------------|
| Storage Temperature | -20 - 70 °C |
| Operating Temperature | -10 - 60 °C |

Übertragungstechnische Eigenschaften

| | |
|------------|---------------|
| Wavelength | 850 - 1300 nm |
|------------|---------------|