

Caja de terminación Pau fibra 4 salidas SC Simplex

Ref.: PAU4F



General data

Application:

Optical Telecommunication Networks
LAN, Optical fiber Communication Network
CATV Networks
FTTH access Network
PON, G-PON

Delivery unassembled (4x shrink protection and material for wall mounting included)

When using crimp splice protection, please note that these cannot be firmly inserted

Allgemeine Daten

Holder for splitter	False
With Fiber overlength cassette	True
Suitable for adapter	SC Simplex/LC Duplex/E2000®
Number of Fibres	4
Scope of application	Indoor
Mounting method	Wall mounting

Caja de terminación Pau fibra 4 salidas SC Simplex

Ref.: PAU4F

Holder for gas blocker	False
Type of Splice protection	Thermo
Possibility of mast mounting	False

General data

Colour	white
Max. Assembly (Adapter)	4
Cable sheath support	False
Hinged splice cassette	True

Mechanical characteristics

IP Protection	IP20
Foreign body and contact protection	Protection against medium-sized foreign bodies

Mechanische Eigenschaften

Water protection	Without protection
------------------	--------------------

Abmessungen

Dimension	150 x 110 x 34 mm
-----------	-------------------

Environmental conditions

Temperature range	0 - 50 °C
-------------------	-----------

Caja de terminación Pau fibra 4 salidas SC Simplex

Ref.: PAU4F

