


Cable 48Fo SM 9/125

Multitubo Arm. Diel. Int/Ext.

LSZH-B2ca



General data

Fields of application:
 For building connections
 For campus cabling
 For use in plastic pipe systems
 For installation in cable ducts and on flatbeds

Characteristics:

Easy to use construction
 Gel-free cable construction for clean and fast assembly
 Small dimensions
 High laying stability
 Fire behaviour tested and certified according to
 Construction Products Regulation (see Euro fire class)

Cable diameter may vary

Allgemeine Daten

Cable metal free	True
Armouring	True
Blow in	False
Material outer sheath	LSZH
With strain relief	True
Colour outer sheath	yellow
Application	Inside
Cable silicone free	True

Cable 48Fo SM 9/125

Multitubo Arm. Diel. Int/Ext.

LSZH-B2ca

Mechanische Eigenschaften

Crush resistance	1000 N/dm
------------------	-----------

Kabelaufbau

Fiber marking	Colour
Tube marking	Colour
Fibre type	Single mode 9/125
Fibre category	G657.A1

Kabelmantel

Flame retardant	According to EN 60332-1-2
Euro Class	B2ca

Umgebungsbedingungen

Temperature Range (Installation)	-5 - 50 °C
Temperature Range (Storage)	-25 - 70 °C
Temperature Range (Operation)	-25 - 60 °C

Normen, Zulassungen, Zertifizierungen

Harmonised Standard	EN 50575
With rodent protection	True